

ALFOMBRA MODULAR

COLECCIÓN PULSE


TUNTEX

DESCRIPCIÓN


Nuestra *Colección Pulse* está diseñada para crear una atmósfera interior positiva, abierta e inspiradora. Su concepto estético refleja el ritmo constante de un pulso generando una **cadencia única al espacio** y promoviendo un ambiente acogedor. Confeccionado con fibra NEXLON™ un nylon de primera calidad teñido en masa.




COLOR & TEXTURA



Rose
T10511



Pebble
T10509



Admiral
T10515




Lead
T10510




Shamrock
T10513


SUGERENCIA DE INSTALACIÓN



Cuarto de vuelta,
Quarter Turn



Sillar



Ladrillo, Brick



TECNOLOGÍA
STAINSHIELD™



GRAN DURABILIDAD



AMIGABLE CON EL
MEDIO AMBIENTE



FIBRA TECNOLOGÍA
NEXLON™



FÁCIL REEMPLAZO



FÁCIL INSTALACIÓN



VERSATILIDAD
EN DISEÑO

VENTAJAS

omv

• Soluciones Arquitectónicas •

✉ info@omvdeco.cl | 🌐 www.omvdeco.cl | 📞 Fono: +56 232244414 / Cel: +56 944667207

| 01

ALFOMBRA MODULAR

COLECCIÓN PULSE

TUNTEX

CARACTERÍSTICAS TÉCNICAS

PRODUCT SPECIFICATIONS	
Style	Pulse
Style Number	T 105
Pile Fibre	Nexlon™ Premium Solution Dyed Nylon
Dye Method	Solution Dyed
Gauge	1 / 12G
Pile Height	4.5- 3.5mm
Total Thickness	7.2mm (0.5mm)
Total Weight	Approx 4950 g/m ²
Secondary Back	TUNTEX Duraback
Stain Resistance	Stainshield Treatment: STAINSHIELD™
Soil Resistance	Soil Guard Treatment: SOILGUARD™
Construction	Multi Hi / Lo Loop
Tile size	500mm x 500mm

Wear Warranty	Product is warranted not to lose more than 10% pile fibre by weight in normal commercial use within 15 years
Colour Fastness	15 Year Warranty AATCC 16. Grade 4 - Little or no change.
Static Electricity	Permanent Lifetime Protection - less than 2.0 KV
Dimensional Stability	Warranted not to change in size by more than 0.5 mm in normal use. Will not dome or dish in normal use.
Installation	Tackifier or Releasable adhesive Recommended.
Sustainability	All yarns used are Solution dyed to minimise use of water and exclude any effluent production. ISO 14001 and ISO 9001.

